

Vacuum packing machine

Vacuum packer « VC 999 »

Datasheet, 17.05.2023, V1.1

 Engineered and made in Switzerland



Machine functions

- 6 models proposed :
 - Standard : K2, K3 or K4
 - With predisposition pour inert gas K2N, K3N or K4N
- Low space requirement
- Double welding line
- Several programs available
- Low maintenance
- Machine frame in stainless steel
- Options :
 - Rolling frame, furniture (*except K4 as standard*)
 - Inert gas device



Technical specifications

	K2	K3	K4
Supply voltage:	230 V / 50 Hz	230 V / 50 Hz	400 V / 3/50 Hz
Power :	800 W	1'300 W	1'500 W
Welding length :	325 mm	470 mm	470 mm
Pump flow rate :	8 m ³ / h	20 m ³ / h	60 m ³ / h
Weight :	50 kg	72 kg	135 kg
Useful inside dimensions (l/d/h) :	340 x 330 x 130 mm	480 x 380 x 150 mm	480 x 530 x 180 mm
Outside dimensions (l/d/h) :	375 x 560 x 350 mm	520 x 590 x 372 mm	520 x 765 x 1'036 mm
Inert gas device :	Option	Option	Option
Rolling frame :	Option	Option	Standard